

Product Data Sheet

Knauf Joint Cement Premium



Knauf Joint Cement Premium is a lightweight air-drying compound, for bedding tapes and finishing joints by hand or machine application. Up to a Q3 finish.

Areas of Application

For jointing of gypsum boards. For bedding joint tapes and finishing joints by hand or machine application.

Key Benefits

- Exceptional finish
- Minimal sanding effort
- 12 months shelf life

Compliance Standards

EN13963. Type 3A.

Performance Data

Reaction to Fire (R2F)	Flexural Strength (F)	Dangerous Substances (DS)
A2-s1,d0	NPD	NPD

Technical information

Colour	Weight (kg)	Approximate Coverage	Material Number
White/grey	20	72m ² per 20kg bag*	622337

*Based on filling application to tapered edge board

Sustainability

Substances of very high Concern (SVHC)

At the time of publication, under REACH UK and REACH EU regulations this product contains no SVHC. For more information please consult the Safety Data Sheet.

Storage and Handling

Store in a dry area, protected from frost, high temperature and exposure to direct sunlight. Storage and application temperature to be above 5°C.

Packaging

Paper sack with an inner plastic layer for protection

Shelf Life/Service Life

12 months.

Disposal/Repair

Dispose of contents/container in accordance with licensed collectors sorting instructions.

Health & Safety

Impermeable protective gloves, safety glasses with side shields due to splashing, and a dust mask when sanding are recommended. For full information, please refer to the safety data sheet.


Application / Installation

Add the powder to 8.8L per 20kg bag of cold, clean water in a suitable clean mixing container. Mix to workable consistency. Drying time approximately 24 hours depending on conditions. When dry, apply second coat. If sanding is required, at least 120-180 grit depending on hand or machine sanding. Once the jointing is completed and dry, a coat of Knauf Wallboard Primer or Knauf Plasterboard Sealer should be applied before decoration. For detailed application advice, consult BS 8000-8 2023.

Additional Documentation

[Declaration of Performance UKCA](#)

[Declaration of Performance CE](#)



Customer Service

UK Tel: 0800 521 050
Eire Tel: 01 4620739
Email: cservice@knauf.com

Technical Service

0800 521050 (option 2)
Live Webchat 09:00 -17:00
technical-uk@knauf.com

Website

www.knauf.co.uk
www.knauf.ie

Address (UK)

Knauf
Kemsley Fields Business Park
Sittingbourne
Kent ME9 8SR

Address (Ireland)

Knauf
87 Broomhill Road
Tallaght
Dublin 24
D24 WR85

KML100447

The information given in this publication is believed to be current and accurate as at the date of publication, but no warranty, express or implied is given. Updates will not be automatically issued.

© Copyright Knauf 2023

Creation Date: 02/11/2023

Revision Reference: 001

Revision Date: 02/11/2023